

DEFENDER EXTENSION LEADS SPECIFICATION SHEET



birchwood
products ltd

PRODUCT: DEFENDER EXTENSION LEADS
PART NO.:

Iss. 01 Iss. Date 10/07/06

14M EXTENSION LEAD

The Defender Arctic grade extension lead has been specifically designed to offer flexibility at lower temperatures (-20°C) whilst maintaining durable qualities under normal working conditions.

Defender plugs have many great features to ensure a safer working environment. A specially designed 'high point' earth wire connector guards against electrocution. The inverted waterproof grommet ensures that water's kept out of the unit. The addition of a suspension point allows you to keep the component off the ground and out of harm's way in fixed installations

INPUT VOLTAGE	110V
RATED OUTPUT VOLTAGE	300/500V
AMPERAGE	16A
PLUG & COUPLER	DEFENDER 110V 16A - MADE TO BS 60309 - 3 PIN FYELLOW FOR EASY SITE IDENTIFICATION
CABLE	3G1.5MM ² H05 VV-F ARTIC GRADE (MANUFACTURED TO VDE 0281) 49 X 0.26 STRANDS 3.9MM (+/- 0.1) INSULATION DIAMETER 1.1MM SHEATH
OPERATING TEMP.	From -20C TO 70C
IP RATING	IP44
WEIGHT	
PACKAGING	
PRICE	



Defender
POWER AND LIGHT